

PROJEKT PRIMER



Primer for walls and ceiling in interior use

- Good adhesion
- High coverage and whiteness
- Easy to apply with minimal splashing

Product description

Full matt water-borne primer for walls and ceiling, interior use. The paint is easy to apply, does not splash when rolling, ideal for smoothing absorption of uneven surfaces and ensuring an even finish painting. It can be used for painting concrete, plaster, putty, plasterboard, fiberboard and chipboard, paintable wallpaper, as well as previously painted surfaces.

The primer has a very good covering and filling power, ensuring a uniform gloss of the surface color even after a single recoating. Projekt Primer prepares a flat, smooth surface and reduces topcoat paint consumption.



Swedish paint
Since 1955

Area of application	Indoors
Binder	VAE
Volume Solids	37%
Weight Solids	58%
Density	1.43 kg/l
Viscosity	180 cP
Gloss	2-3 (full matt)
Thinner/Cleaning	Water
Material consumption	ca 7-12 m ² /l depends on the application method, conditions, shape and roughness of the surface to be treated
Temperature at painting	+5° - +30°C
Tools for painting	Brush/roller/spray
Dust dry	Ca 1 h (20°C, 60%RF)
Re-paintable	3 h
Completely dry	24 h
Shelf life	2 years
Colour	white
Transportation	Protect from frost

How to use

Surface preparation and application conditions

Mechanically remove peeling paint from previously painted surfaces. Surfaces painted with chalk or lime paint, as well as crumbling and highly absorbent surfaces, must be mechanically cleaned and primed with MICRO Tiefgrund. Disinfect mouldy surfaces using a special agent according to the instructions for use. Areas damaged by moisture or yellowed from nicotine should be primed with a special priming paint. Prime metal parts or rusting screws with an anti-corrosion primer. Wash new galvanized surfaces with a suitable detergent and degreaser. Glossy and very smooth surfaces should be sanded matte with sandpaper. If necessary, putty and level the surface with a high-quality putty. The surface to be painted must be clean, dry and uniform.

During painting, air and surface temperature cannot be lower than +5°C and air humidity cannot exceed 80%.

Application

Mix the paint thoroughly before use. The paint is ready for use, but if necessary, it can be slightly diluted with water. To avoid the difference in shades, mix all the required amount of paint in one container, or continuously refill the paint container in use with paint from the next can.

Paint with a brush or roll. When painting with a sprayer, dilute the paint with a bit of water. Repaint after 3 hours. Allow the surface to dry well before applying the next layer.

To avoid paint joint lines, follow the "wet-on-wet" method when painting, applying the coating in one go without stops. Use enough paint on the roller so that the colour is even. If you are right-handed, paint the wall from left to right across the entire surface from bottom to top. If you are left-handed, from right to left respectively. When painting the ceiling, paint in a cross pattern, but paint the last layer in the direction of the light.

Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture.

Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe instruments thoroughly before washing with water. Close the jar carefully after use and keep it

out of the reach of children. Liquid residues must not be drained into the sewer but must be taken to a local collection point.

Recycle empty, dry cans or dispose them of in accordance with local regulations.

Protect the environment, like we do!

Keep out of reach of children. Contains biocidal products: BIT, C(M)IT/MIT (3:1). May produce an allergic reaction.

This product contains a maximum of 30 g VOC/L. The limit value is 30 g VOC/L (cat. A/a).

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.