

Wall 4

Wall paint

Helps to hide small imperfections

Easy to paint

Easy to clean

Full matt (4) waterborne easily cleanable (class 1 according to EN 13300) paint for interior applications. It leaves a smooth full matt surface and gives flawless result. Green Line paints are certified by Nordic Swan Ecolabel and approved by Asthma and Allergy Association. Products contain minimum amount of volatile organic compounds (VOC)



TECHNICAL DATA	
Fields of application	Walls and ceilings in dry premises (bedrooms, children's rooms, living rooms, offices, schools, kindergartens and other public premises). Suitable for new and previously painted gypsum boards, filler-treated and wallpapered surfaces.
Gloss	Full matt
Coverage (per coat)	10-12 m ² /l – previously painted smooth surfaces, 7-9 m ² /l – gypsum boards and filler-treated rough surfaces,
Tinting	Paint can be used white (base A), tinted in light shades (base A) or dark shades (base C) according to Tikkurila interior color cards. Use Color Test can for choosing the suitable shade. Tinted products cannot be returned or exchanged.
Base paints	A BASE, C BASE
Application method	To be applied with a roller, painting brush or high pressure airbrush. Suggested working tools: Anza rollers Platinum Micmex or Basic Rilón.
Drying time (at +23 °C, relative air humidity 50%)	Touch dry - 0,5 hours, recoatable - 1-2 hours.
Thinner	Water. The amount of thinner may be up to 10% of the paint volume.
Cleaning of painting tools	Clean painting instruments from liquid paint residue, then wash with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint
Storage	Protect the product from frost!
Storage time	In tightly closed original container until best before date. Production/ best before dates are stated on a can. Reseal once opened cans well for next use.



TECHNICAL DATA	
Solid content	About 37% v/v.
Density	1,2 -1,3 kg/l, depending on the colour shade.
Wet scrub resistance	Class 1, ISO 11998, 200 cycles 5 microns.
Resistance to chemicals	Resistant to short-term exposure to household cleansers and weak solvents (white spirit).
Packaging	A BASE: 0.9 l, 2.7 l, 7.2 l, 11.7 l, 18 l C BASE: 0.9 l, 2.7 l, 7.2 l, 11.7 l

INSTRUCTIONS FOR USE

PREPARATION

Unpainted surfaces:

Clean the surface from dust and dirt. Use suitable filler from Vivacolor series to treat uneven surface, sand the surface and remove the dust formed. Filler-treated, porous or non-uniformly absorbing surfaces, as well as fibreboard- or cardboard surfaces shall be primed with waterborne priming paint Primer 1. Prime metal surface (e.g nail heads) with priming paint for metals Universal Korrostop. Use alkyd priming paint Special Primer to prime surfaces treated with chalk-based whitening putty. When using any priming paint, follow relevant guidance for the product's use. Using priming paint will reduce consumption of topcoat paint and improve adhesion between surface and topcoat.

Previously painted surfaces:

Remove residues of old loose paint. Clean the surface with cleansing agent Special Clean, rinse it with water and allow to dry. Sand glossy and hard surface until matt, remove dust. Weak and dusty surfaces should be treated with alkyd priming paint Special Primer. Use suitable filler from Vivacolor series to treat chinks and cracks, sand the surface and remove the dust formed. Prime filler-treated surfaces with waterborne priming paint Primer 1.

Painting condition

Surface should be clean and dry, temperature of ambient air should be above +5 °C and relative air humidity lower than 80%. Avoid draught and high temperatures during painting.

Painting

Thoroughly mix paint Wall 4 before painting, thin with water if required up to 10% of volume. To obtain uniform and monochromatic coating, sufficient amount of colour-shaded paint should be mixed in one vessel prior painting. Apply 1 or 2 layers with roller, brush or airbrush.

CARE AND HANDLING OF SURFACE

The surfaces can be cleaned in 1 month after painting. To clean the surface, use a sponge or a cloth, moistened with water or a solution of a neutral cleansing agent (pH 6-8). To clean heavily soiled surfaces, use a sponge or a cloth, moistened with the solution of a low-alkali cleansing agent (pH 8-10). After cleaning, rinse the surface with clean water. On preparing the solution, follow the manufacturer's instruction. After painting, the surfaces should not be heavily loaded, for under normal conditions the painted surface will gain its ultimate endurance and resistance to wear in approximately 1 month after painting. If the surface still needs cleaning prior to this time, it can be delicately cleaned with a sponge or cloth, moistened with water.

ENVIRONMENTAL, SAFETY AND WASTE REGULATORY

Contains: 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)) May cause an allergic skin reaction. Wear protective gloves.

Do not pour liquid waste into drains. Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations for hazardous waste. Avoid spillage into drains, water systems and soil. This product contains a biocidal product for the preservation of the product during storage. EU VOC limit value (subgroup A/a): 30 g/l. Maximum content of VOC in product is 2g/l.

TRANSPORTATION

Protect from frost

ADDITIONAL PRODUCT INFORMATION

www.vivacolor.ee www.vivacolor.lv www.vivacolor.lt