

Briljant

Product description:

Briljant is a distinctly elegant premium paint for indoor wood surfaces. The enamel is available in 4 different levels of gloss: matte, semi-matt/semi-glossy/glossy, all equal in quality. Briljant provides a beautiful and highly-durable surface for woodwork, panelling, furniture, mouldings, window frames and doors.

The paint, which gives a beautiful and extremely durable surface, has very good spread characteristics which make it easy to obtain a smooth surface that is also tough and washable. Exposed surfaces are able to withstand everyday wear and tear and remains beautiful for a long time.

It's a part of Hagemans Nordic tinting system.

TECHNICAL DATA:

Area of application	Indoor
Binder	PU alkyd / acrylic
Volume Solids	37%
Weight Solids	52%
Density	1,30
Washability	Class 1
Spreading rate	9,4 (RAL 9010)
Material consumption	8–10
Thinner/Cleaning	Water
Temperature at painting	Minimum +5°C
Tools for painting	Brush, enamel-roller and spray
Dust dry	2 h
Re-paintable	8 h
Completely dry	48 h
Flammability	Not flammable
VOC category	(Cat A/d): 130 g/l

HOW TO USE

Pre-painting:

Always start by reading the instructions on the tin. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Apply under controlled conditions, where air-, paint- and surface temperature may not be below +5°C. High humidity will prolong the drying time.

Protect floor and furniture properly. Stir the paint properly from the bottom before starting painting.

The substrate which shall be painted shall be clean, with good adhesion, dry and dust free. Wash, flush and remove old paint with bad adhesion.

Painting:

The paint is ready to use. Apply with brush or suitable enamel roller. After light diluting with water, it can also be applied by spraying. When applying by spray, use appropriate respiratory protection. Smoothen with enamel brush.

Disturbing discrepancies in nuance will be avoided if you paint the coherent surfaces with paint from the same tin. This concerns especially tinted paint. When this is not possible, then use tins with same batch number, which can be read on the label.

Post-painting:

Wipe off the tools thoroughly before cleaning in water and a mild cleaning liquid. Seal the tin carefully after use and keep out of reach for children. Recover unused paint for re-use.

Reuse of paint can effectively minimise the products' life cycle environmental impact.

Liquid residues may not be poured down the drain, but be submitted to the local collection point.

Maintenance:

Be careful when cleaning surfaces with acrylic paint with lower gloss, since the paint has a more sensitive finish. Use a damp rag and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.