# Colorex

### **Proper Decking stain**



**TECHNICAL PRODUCT DATA SHEET** 

2022-10-26

Page 1/2

#### Product description:

Proper Decking stain is solvent based, transparent silicon alkyd oil stain on solvent base, particularly intended for water proof treated wood outdoors. The stain is suitable for outdoor use – terraces, garden decors and furniture, wherever a transparent or a nuanced stain surface is desired.

Proper Decking stain prevents the wood from cracking and dehydration. It is also suitable for hard exotic wood, such as teak.

This product has the highest UV resistance, penetration and water resistance. It contains biocides to protect against mould.

Proper Decking stain is produced in Sweden and included in Colorex Mix tinting system.

#### **TECHNICAL DATA:**

Area of application Outdoors

Binder Silicon alkyd, Alkyd and Tung tree oil

Volume Solids 30%
Weight Solids 35%
Density 0,86 kg/l

Thinner/Cleaning White spirit/Naphtha

Material consumption 4–7 m<sup>2</sup>/L. sawn wood, 7–12 m<sup>2</sup>/L. planed wood

Temperature at painting Minimum +5°C

Tools for painting Brush, dipping or cloth

Dust dry 8 h
Re-paintable 16 h
Colour Clear
Flammability 3

VOC category (Cat. A/f): 700 g/l (2010)

#### How to use

#### **Pre-painting**

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.

The surface must be clean, dry and firm. Scrape off loose, porous and degraded wood. Air and surface temperature is also important for the end result. Do not paint if it is below +5°C.

Hagmans Nordic AB
Box 112, 511 10 Fritsla
Telefon: +4632018900
order@hagmansnordic.com

Version: 2022-10-26 12:13



## Proper Decking stain



**TECHNICAL PRODUCT DATA SHEET** 

2022-10-26

Page 2/2

#### **Painting**

Apply Proper by brush, cloth or by dipping until the wood stops absorbing. Wipe off the excess after a few minutes with a cloth or a sponge. Let dry and repeat the treatment if necessary. The product is supposed to penetrate into the surface and not be as a film on top.

The high dry content makes that Proper is not suitable as primer when coating with paint.

#### Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, we do.

**N.B.!** Cloths soaked in stain may spontaneously combust and must therefore be neutralised.

#### **Maintenance**

Can be cleaned with a soft scrub brush and possibly a little mild detergent solution.

Hagmans Nordic AB Box 112, 511 10 Fritsla Telefon: +4632018900 order@hagmansnordic.com Version: 2022-10-26 12:13