Hagmans Golvfärg 1K

Replaces date: 08/12/2022

Revision date: 07/06/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name:

Hagmans Golvfärg 1K

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses:

1.3. Details of the supplier of the safety data sheet

Paint

Supplier

Supplier	
Company:	Hagmans Nordic AB
Address:	Box 112
Zip code:	511 10
City:	Fritsla
Country:	SWEDEN
E-mail:	info@hagmansnordic.com
Phone:	+46(0)320-18900
Homepage:	www.hagmans.com

1.4. Emergency Telephone Number

Members of the public: 111 (NHS 111 (Scotland: NHS 24)).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification:	The product shall not be classified as hazardous according to the classification and labeling rules for substance and mixtures.
2.2. Label elements	
Supplemental information	
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3- one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
Contains biocidal products: BIT,	C(M)IT/MIT (3:1) May produce an allergic reaction.
VOC:	This product contains a maximum of 140 g VOC/L. The limit value is 140 g VOC/L (cat. A/i)
2.3 Other hazards	

2.3. Other hazards

The product does not contain any PBT or vPvB substances. Endocrine disrupting properties: None known.

Hagmans Golvfärg 1K

Replaces date: 08/12/2022

Revision date: 07/06/2023

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Eye Irrit. 2;H319 Acute Tox. 4;H302
Acute Tox 4:H302
Cite ToX. *, 1/315 Skin Iriti. 2;H315 Skin Sens. 1;H317 Eye Dam. 1;H318 Acute ToX. 2;H330 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 C ≥ 0.05%: Skin Sens. 1; H317 LD50 (Acute toxicity - oral): 490
Imp/kg bw Acute Tox. 3;H301 Acute Tox. 2;H310 Skin Corr. 1B;H310 Skin Corr. 1B;H311 Skin Sens. 1A;H317 Eye Dam. 1;H318 Acute Tox. 2;H330 Aquatic Acute 1;H400 Aquatic Acute 1;H400 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 EUH071 C ≥ 0.0015%: Skin Sens. 1A;H317 C ≥ 0.6%: Eye Dam. 1;H318 C ≥ 0.6%: Skin Corr. 1C;H314 0.06% ≤ C < 0.6%: Skin Irrit. 2;H319

Please see section 16 for the full text of H- / EUH-phrases.

Ingredient comments:

Some products in this product range contain \geq 1% titanium dioxide (13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:	Seek fresh air.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
Skin contact:	Wash skin with soap and water. Seek medical advice in case of persistent discomfort.
Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
General:	When obtaining medical advice, show the safety data sheet or label.
4.2 Most important sympto	ms and offects, both acute and delayed

4.2. Most important symptoms and effects, both acute and delayed

The product contains substances that in some cases can cause an allergic reaction on skin contact.

Hagmans Golvfärg 1K

Replaces date: 08/12/2022

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: The product is not directly flammable. Choose extinguishing agents based on the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None known.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Wear suitable protective clothing. Keep unnecessary personnel away.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

All work must be carried out under well-ventilated conditions. Wash hands before breaks, before using restroom facilities, and at the end of work. Do not eat, drink or smoke during work.

7.2. Conditions for safe storage, including any incompatibilities

Store safely and keep out of reach of children. Store in a dry, cool, well-ventilated area. Store frost-free.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

SECTION 8: Exposure controls/personal protection

Revision date: 07/06/2023

Hagmans Golvfärg 1K

Replaces date: 08/12/2022

Revision date: 07/06/2023

8.1. Control parameters

Occupational	exposure innit					
Substance name	Time period	ppm	mg/m³	fiber/cm3	Remarks	Comments
2-(2- butoxyethoxy) ethanol	15m	15	101.2			
2-(2- butoxyethoxy) ethanol	8h	10	67.5			

8.2. Exposure controls

Appropriate engineering
controls:Provide good ventilation.Personal protective equipment,
eye/face protection:Wear safety goggles if there is a risk of eye splash.Personal protective equipment,
skin protection:Wear suitable protective clothing.Personal protective equipment,
skin protection:Heavy use, longterm contact (more than 2 hours): In the event of direct skin contact, wear
protective gloves:

Personal protective equipment, In case of insufficient ventilation, wear respiratory protective equipment. respiratory protection:

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit	
State	Viscous liquid.	
Colour	According to product specification	
Odour	Characteristic	
Solubility	Solubility in water: Soluble	

Hagmans Golvfärg 1K

Revision date: 07/06/2023

Parameter	Value/unit	Remarks
Odour threshold		Not applicable.
Melting point	~ 0 °C	Water
Freezing point	~ 0 °C	Water
Initial boiling point and boiling range	~ 100 °C	Not specified
Flammability (solid, gas)		Non-flammable
Flammability limits	No data	
Explosion limits		Non-explosive
Flash Point		Not relevant Waterborne paint
Auto-ignition temperature		Not relevant Waterborne paint
Decomposition temperature	No data	
pH (solution for use)	~ 8	
pH (concentrate)		Not relevant
Kinematic viscosity	No data	
Viscosity	> 20.5 mm2/s	
Partition coefficient n-octonol/water		Not relevant Waterborne paint
Vapour pressure	No data	
Density	~1200 kg/m³	
Relative density	No data	
Vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Replaces date: 08/12/2022

Parameter	Value/unit	Remarks
Explosive properties		Non-explosive
Oxidising properties		Non-oxidising.

SECTION 10: Stability and reactivity

10.1. Reactivity

No known data.

10.2. Chemical stability

Stable under recommended storage and handling conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid temperatures < 5°C.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

5/8

Hagmans Golvfärg 1K

Revision date: 07/06/2023 Replaces date: 08/12/2022 Acute toxicity - oral: Based on existing data, the classification criteria are deemed not to have been met. Acute toxicity - dermal: Based on existing data, the classification criteria are deemed not to have been met. Acute toxicity - inhalation: Based on existing data, the classification criteria are deemed not to have been met. Skin corrosion/irritation: Based on existing data, the classification criteria are deemed not to have been met. Serious eye damage/eye Based on existing data, the classification criteria are deemed not to have been met. irritation: Respiratory sensitisation or Based on existing data, the classification criteria are deemed not to have been met. skin sensitisation: The product contains small amounts of 1,2-benzisothiazol-3(2H)-one, reaction mass of 5chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). Persons with a known allergy may exhibit an allergic response to the product. Germ cell mutagenicity: Based on existing data, the classification criteria are deemed not to have been met. Carcinogenic properties: Based on existing data, the classification criteria are deemed not to have been met. **Reproductive toxicity:** Based on existing data, the classification criteria are deemed not to have been met. Single STOT exposure: Based on existing data, the classification criteria are deemed not to have been met. Repeated STOT exposure: Based on existing data, the classification criteria are deemed not to have been met. Aspiration hazard: Based on existing data, the classification criteria are deemed not to have been met. 11.2. Information on other hazards

Endocrine disrupting	Constituents have no endocrine-disrupting properties with respect to non-target organisms
properties:	as they do not meet the criteria in Section B of Regulation (EU) 2017/2100.

SECTION 12: Ecological information

12.1. Toxicity

Based on existing data, the classification criteria are deemed not to have been met.

12.2. Persistence and degradability

Test data are not available. Expected to be biodegradable.

12.3. Bioaccumulative potential

Test data are not available. No bioaccumulation expected.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

Constituents have no endocrine-disrupting properties with respect to non-target organisms as they do not meet the criteria in Section B of Regulation (EU) 2017/2100.

12.7. Other adverse effects

None known.

Hagmans Golvfärg 1K

Replaces date: 08/12/2022

Revision date: 07/06/2023

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not discharge large quantities of concentrated spills and residue into drains. Avoid unnecessary release to the environment. Empty, cleansed packaging should be disposed of for recycling.

Category of waste:	EWC code: Depends on line of business and use, for instance
	08 01 12 waste paint and varnish other than those mentioned in 08 01 11
	20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

SECTION 14: Transport information

14.1. UN number or ID number: 14.2. UN proper shipping name:	Not applicable. Not applicable.	14.4. Packing group: 14.5. Environmental hazards:	Not applicable. Not applicable.
14.3. Transport hazard class(es):	Not applicable.		

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment		
Other Information:	Chemical safety assessment has not been performed.	
SECTION 16: Other i	nformation	
Other Information:	This safety data sheet has been prepared for and applies to this product only. It is based on	

our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with Regulation 1907/2006/EC "The Registration, Evaluation and Authorization of Chemicals" as amended by the stationary UK REACH etc. (EU Exit) as subsequently changed.

Vendor notes: Changes have been made in sections: 3, 16.

Hagmans Golvfärg 1K

Revision date: 07/06/2023

Replaces date: 08/12/2022

Hazard statements		
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H310	Fatal in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
Our alemental harvard information		

Supplemental hazard information

GB

EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Country: