Conforms to Regulation (EC) No.	1907/2006 (REACH), /	Annex II, as amended by	Commission Regulation (EU)
2015/830 - Europe			

Date of issue/ Date of revision

: 12/8/2017

Date of previous issue

: 7/13/2016



SAFETY DATA SHEET

ULTRA PRO 30

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	:
Product description	:

- : ULTRA PRO 30
- : A waterborne acrylate paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor		
Tikkurila Oyj		
P.O. Box 53		
FI-01301 VANTAA		
FINLAND		
Telephone +358 20 191 2000		
e-mail address of person	1	Tikkurila Oyj,
responsible for this SDS		Product Safety,
-		e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number	: 112 (24h)
Supplier or Manufacturer	
Telephone number	: I ∕ikkurila Oyj +358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance	or mixture
Product definition : Mi	xture
Classification according to Regul	ation (EC) No. 1272/2008 [CLP/GHS]
Skin Sens. 1, H317	
Aquatic Chronic 3, H412	
The product is classified as hazardo	us according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements Hazard pictograms	
Signal word	: Warning
Hazard statements	: H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	: Not applicable.

Date of issue/Date of revision	08.12.2017 Date of previous issue 13.07.2016. ULTRA PRO 30
Prevention	 P261 - Avoid breathing mist/spray. P273 - Avoid release to the environment. P280 - Wear protective gloves. P284 - In case of inadequate ventilation wear respiratory protection.
Response	: P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: 2-octyl-2H-isothiazol-3-one (OIT)
Supplemental label elements	 Contains small amounts of sensitizing substances: 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 3-iodo-2-propynyl butylcarbamate (IPBC)
Treated articles	

This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1).

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture			
			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-
3-iodo-2-propynyl butylcarbamate (IPBC)	EC: 259-627-5 CAS: 55406-53-6	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-
2-octyl-2H-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	-
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	CAS: 55965-84-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Date of issue/Date of revision	08.12.2017 Date of previous is	sue 13.07.2016.	ULTRA PRO 30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

 In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
 Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
: Remove to fresh air. Keep person warm and at rest.
 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Get medical attention if symptoms occur.
: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	se an extinguishing agent suitable for the surrounding fire. Recommended lcohol resistant foam, CO ₂ , powders or water spray/mist.	1:
Unsuitable extinguishing media	o not use a direct water jet that could spread the fire.	
5.2 Special hazards arising f	ne substance or mixture	
Hazards from the substance or mixture	his product is not classified as flammable. Fire will produce dense black sr xposure to decomposition products may cause a health hazard.	noke.
Hazardous combustion products	\bar{l} hen exposed to high temperatures, hazardous decomposition products maroduced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	se water spray to keep fire-exposed containers cool. This material is haza quatic organisms. Fire water contaminated with this material must be containd prevented from being discharged to any waterway, sewer or drain.	
Special protective equipment for fire-fighters	ire-fighters should wear appropriate protective equipment and self-containe reathing apparatus (SCBA) with a full face-piece operated in positive press node.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	:	Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	:	Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	: Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities	: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.

7.3 Specific end use(s) : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-methoxymethylethoxy)propanol	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m ³ 8 hours.

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

ate of issue/Date of revision	0	8.12.2017 Date of previous issue	13.07.2016.	ULTRA PRO 30
Individual protection mea	sures			
Eye/face protection	: L	Jse safety eyewear (EN166), es	pecially during s	pray-application.
Hand protection	r ir n F >	 Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves 		
Skin protection	: V	Vear suitable protective clothing].	
Respiratory protection	c re E fe c	 If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a half mask or full fact respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:19) EN405:2001). During continuous and long-term work the use of motor-driven or fed respirators is recommended (EN12941:1998). Be sure to use an approved certified respirator or equivalent. Check that mask fits tightly and change filter regularly. 		 Wear a half mask or full face er P2 during sanding (EN140:1998, work the use of motor-driven or air-). Be sure to use an approved/
En la companya da la comp	-			

Environmental exposure : For in controls section

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	:	Coloured
Odor	:	Mild.
Odor threshold	:	Not relevant for the hazard assessment of the product.
рН	:	Not relevant for the hazard assessment of the product.
Melting point/freezing point	:	Not available.
Initial boiling point and	:	Not available.
boiling range		
Flash point		>100°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Density	:	1.1 to 1.2 g/cm ³
Solubility(ies)	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not relevant for the hazard assessment of the product.
Viscosity	:	Not relevant for the hazard assessment of the product.
Explosive properties	:	No explosive ingredients present.
Oxidizing properties	:	No oxidizing ingredients present.

9.2 Other information

No additional information.

08.12.2017 Date of previous issue

ULTRA PRO 30

13.07.2016.

SECTION 10: Stabilit	y	and reactivity
10.1 Reactivity	1	See Section 10.5.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid extreme heat and freezing.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis
10.6 Hazardous decomposition products	:	When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Fiodo-2-propynyl butylcarbamate (IPBC)	LD50 Oral	Rat	1470 mg/kg	-
2-octyl-2H-isothiazol-3-one (OIT)	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-
1,2-benzisothiazol-3(2H)- one (BIT)	LD50 Oral	Rat	1020 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) (C(M)IT/MIT (3:1))	LD50 Oral	Rat	53 mg/kg	-

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

May cause an allergic skin reaction. Contains following preservatives or other biocides: 1,2-benzisothiazol-3(2H)-one (BIT) reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)) 2-octyl-2H-isothiazol-3-one (OIT) 2-methyl-2H-isothiazol-3-one (MIT) 3-iodo-2-propynyl butylcarbamate (IPBC)

Mutagenicity

Not classified.

13.07.2016.

ULTRA PRO 30

Carcinogenicity
Not classified.
Reproductive toxicity
Not classified.
Teratogenicity
Not classified.
Specific target organ toxicity (single exposure)
Not classified.
Specific target organ toxicity (repeated exposure)
Not classified.
Aspiration hazard
Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product. Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
iodo-2-propynyl butylcarbamate (IPBC)	EC50 0.053 mg/l	Algae	72 hours
	EC50 0.16 mg/l	Daphnia	48 hours
	LC50 0.067 mg/l	Fish	96 hours
	NOEC 0.05 mg/l	Daphnia - Daphnia magna	21 days
2-octyl-2H-isothiazol-3-one (OIT)	EC50 0.32 mg/l	Daphnia - Daphnia magna	48 hours
	LC50 0.047 mg/l	Fish - Oncorhynchus mykiss	96 hours
1,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) (C(M)IT/MIT (3:1))	Acute EC50 0.379 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0.16 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.19 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.0012 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.004 mg/l	Daphnia - Daphnia magna	21 days

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Peaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) (C(M)IT/MIT (3:1))	-	-	Readily

12.3 Bioaccumulative

potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
₽-octyl-2H-isothiazol-3-one (OIT)	2.45	-	low
(2-methoxymethylethoxy) propanol	0.004	-	low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11* 08 01 12	waste paint and varnish containing organic solvents or other hazardous substances waste paint and varnish other than those mentioned in 08 01 11
	with other wastes, the original waste product code may no longer apply and the appropriate d. For further information, contact your local waste authority.
Packaging	
Methods of disposal	: Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions

ons : No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

08.12.2017 Date of previous issue

ULTRA PRO 30

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

13.07.2016.

: Not available. 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

: Not determined.
: This product is in scope of Directive 2004/42/CE.
: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative
Procedure used to de	rive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification

Skin Sens. 1, H317 Aquatic Chronic 3, H412 **Justification**

Calculation method Calculation method

Date of issue/Date of revision	08.12.2017 Date of previous issue 13.07.2016. ULTRA PRO 30
Full text of abbreviated H statements	 1 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 4, H302 Acute Tox. 4, H302 Acute Tox. 4, H302 Acute Tox. 4, H400 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Aquatic Chronic 3, H412 Aquatic Chronic 3, H412 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT RE 1, H372 Acute Tox. 3, H301 ACUTE TOXICITY (oral) - Category 3 Acute ToXICITY (oral) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Date of issue/ Date of revision	: 12/8/2017
Date of previous issue Version	: 7/13/2016 : 3

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.