



EcoGun 116

Manual Air Spray Gun Gravity-Feed

Description

This ultra-light, perfectly balanced air spray gun **Eco**Gun 116 with gravity cup is the answer for the application of a wide range of coating media such as top coats, base varnishes and primers and other air

spray materials. It is suitable for coating in the automotive industry, refinish market, machine-plants, furniture industry and many other industrial sectors.



Customer Benefits

- » Nickel plated body for easy cleaning and durability
- Ensured conductivity of the spray gun body for safe grounding
- Perfectly balanced ergonomic shape of spray gun body that minimizes fatigue
- » Easy cleaning and maintenance
- » Wide range of nozzle sizes
- » ATEX EX II 2G T60°C X



EcoGun AS MAN 1GS N36200006V

Specification

Weight	480 g
Material Gun Body	Alumium nickelplated
Parts contacted by media	Aluminium alloy, SST
Connector Fluid	G 3/8" / M16x1,5
Connector Air	1/4" UNI
Recom. Air Pressure	2,0 - 3,0 bar (29 - 44 psi)
Air Pressure max.	4,00 bar (58 psi)
Operating temperature max	60 °C (140 °F)
ATEX Marking	Ex II 2G T60°C X

Accessories


Part No.	Description
M01010185	Connector air D7,2 d10/12 EU
M01010186	Connector air D5 d8/11 US
M01010187	Connector air D7,5 d11/13 Asia
N36960088	Ring kit, 5 colors
N36960038	Cleaning kit EcoGun 22pcs
N36960037	Cleaning kit EcoGun 17pcs
M01300005	Connection air, swivel D5 d8/11 US
M01300006	Connection air, swivel D7,2 d10/12 EU
M01300007	Connection air, swivel D7,5 d11/13 ASIA

Nozzle selection

Air Cap	Nozzle diameters [mm] / Media
AL	1,0 / 1,2 / 1,3 / 1,4* / 1,6 / 1,8* / 2,0 / 2,2* Top coats, base coats, primers, enamels
EL	2,8 General paints, primers or fillers, high flowrate
GL	4,0 General paints, primers or fillers, very high flowrate
* nozzles available also as hardened (for zinc paints)	

* nozzles available also as hardened (for zinc paints,

Characteristics



Further Information

Final weight depending on configuration

If you require further information please do not hesitate to contact our Sales Team at +49 7142 78-0 or Industrial.Products@durr.com