

KOLOREX Wood Paint



Opaque lasyr paint for exterior wooden surfaces

- Copies wood texture
- Extremely weather-resistant
- Mould-protection

Product description

Semi-matte water-based cover lasyr for painting wood outdoors, based on a unique combination of alkyd and acrylate binding agent. Suitable for untreated sawn and planed wooden surfaces as well as for surfaces previously painted with oil and acrylic paints. Contains the biocides that protect the paint film against mould and algae.

KOLOREX Wood Paint has been developed, used and tested for many years in Sweden. In combination with KOLOREX Priming Oil and KOLOREX Primer it provides long-term wood protection.



Swedish paint
Since 1955

Area of application	Outdoors
Binder	Alkyd/akrylat
Volume Solids	36%
Density	1,19 g/cm ³
Viscosity	170cP
Gloss	25 (semi matte)
Washability	Class 1 (EN 13300)
Thinner/Cleaning	Water
Material consumption	6–11 m ² /L depends on the application method, conditions, shape and roughness of the surface to be treated
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and spray
Dust dry	1-2 h
Re-paintable	2-4 h
Completely dry	24 h
Shelf life	2 years in unopened tin, frostless storage
Colour	White (base A) and can be tinted in shades of A, C base without restrictions
Flammability	Not flammable
VOC category	(Cat. A/d): 130 g/l (2010)

KRASO

How to use

Surface preparation and application conditions

The surface must be clean and dry, with the moisture content in the wood less than 18%. Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. Brush or scrape off loose old paint and /or porous and degraded wood. If necessary, wash the surface with a suitable cleaner or water. In case of black mould or algae stains, treat the surface with an anti-mould disinfectant, rinse thoroughly with water, and allow it to dry completely.

Prime untreated wood with KOLOREX Priming Oil according to the product's instructions. While applying primer, pay special attention to the ends of the boards, the places of sawing, location points of screws and nails.

Application

Stir thoroughly before use. Apply one or two coats. For new, previously not treated wood, we recommend at least two coats. Avoid application on hot or sunlit surfaces.

Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture

Environmental and labor protection, waste collection.

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe off the tools thoroughly before cleaning with water. Close the jar carefully after use and keep out of the reach of children. Liquid residues must not be drained into the sewer but must be taken to a local collection point.

Recycle empty, dry cans or dispose them of in accordance with local regulations.

Protect the environment, like we do.

Harmful to aquatic life with long lasting effects. Keep out of reach of children. Avoid release to the environment. Dispose of contents/container in accordance with local regulations.

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.

Contains biocidal products: BIT, C(M)IT/MIT (3:1). Contains a biocidal product for the preservation of dry-film: OIT, diuron (ISO), IPBC. May produce an allergic reaction.

This product contains a maximum of 130 g VOC/L. The limit value is 130 g VOC/L (cat. A/d).